

## Included Components

### 3-angle Valve Job

### As Cast Combustion Chambers

### As Cast Exhaust Ports

### As Cast Intake Ports

11/32" Intake Valve, 2.250" x 5.500" O.A.L	<a href="#">AFR #7620</a>
11/32" Nail Head Exhaust Valve, 1.880" x 5.450" O.A.L.	<a href="#">AFR #7630</a>
PAC Racing #1940 1.550" OD Hydraulic Roller Dual Valve Spring 175 lbs. on seat, .725" maximum lift, Max RPM 6500-6700	<a href="#">AFR #8002</a>
10° Steel Retainers 1.500" O.D x 1.120" I.D x .705" I.D	<a href="#">AFR #8511</a>
10° 11/32" Valve Locks with lashcap recess	<a href="#">AFR #9005</a>
ARP 7/16" Rocker Exhaust Studs	<a href="#">AFR #6406</a>
ARP 7/16" Rocker Intake Studs	<a href="#">AFR #6405</a>
3/8" Guide Plates	<a href="#">AFR #6110</a>
11/32" Viton Valve Seals	<a href="#">AFR #6613</a>
Hardened Valve Spring I.D Locator 1.550" O.D x .705" I.D	<a href="#">AFR #8048</a>