

	Compatible up to 18.5V	Application	Fuel Compatibility	GPH Flow at Rated PSI and 13.5V	Holley Recommendations for Peak Performance				Holley Recommendations for Peak Performance									
					Max HP*		Pump Fitting Size		Minimum Recommended Line Size			Fuel Filter (Carbureted)		Fuel Filter (Fuel injected)		Recommended Regulator		Max Amp Draw
					Naturally Aspirated	Forced Induction	Inlet	Outlet	Inlet	Outlet	Return	Pre	Post	Pre	Post	Carb	EFI	
12-322, 12-325	Yes	Street/Strip	Gasoline/E85	120 @ 8PSI 113 @ 43PSI 100 @ 60PSI	1200 1100 1000	900 850 750	-8AN	-8AN	N/A	-8AN	-8AN	Included	162-564 Optional	Included	162-554 Optional	12-847	12-848	22
12-321, 12-324	Yes	Street/Strip	Gasoline/E85	100 @ 60PSI	1000	750	N/A	-8AN	N/A	-8AN	N/A	N/A	N/A	Included	162-554 Optional	N/A	Included	22
12-320, 12-323	Yes	Street/Strip	Gasoline	60 @ 60 PSI	600	450	N/A	-8AN	N/A	-6AN	N/A	N/A	N/A	Included	162-550 Optional	12-841	12-846	18