Mechanic's Tool Box Set

555-85325 - 170-Piece Set

Set Components

Sockets

- SAE
 - ¹/₄ in. Drive Regular, 6-point
 - $\frac{5}{32}$ in.
 - $^{3}/_{16}$ in.
 - $^{7}/_{32}$ in.
 - ¹/₄ in.
 - $\frac{5}{16}$ in.
 - $^{11}/_{32}$ in.
 - $^{3}/_{8}$ in.
 - $^{7}/_{16}$ in.
 - $^{1}/_{2}$ in.
 - ¹/₄ in. Drive Deep Well, 6-point
 - ¹/₄ in.
 - $9/_{32}$ in.
 - $\frac{5}{16}$ in.
 - ¹¹/₃₂ in.
 - 3/8 in. Drive Regular, 6-point
 - $^{3}/_{8}$ in.
 - ⁷/₁₆ in.
 - $^{1}/_{2}$ in.
 - $9/_{16}$ in.
 - ⁵/₈ in.
 - $^{11}/_{16}$ in.
 - $^{3}/_{4}$ in.
 - ¹³/₁₆ in.
 - 3/8 in. Drive Regular, 6-point
 - $^{3}/_{8}$ in.
 - $^{7}/_{16}$ in.
 - $^{1}/_{2}$ in.
 - $^{9}/_{16}$ in.
 - 5/8 in.
 - 3/8 in. Drive Regular, 6-point
 - $^{3}/_{8}$ in.
 - $^{7}/_{16}$ in.
 - $^{1}/_{2}$ in.
 - $9/_{16}$ in.
 - 3/8 in. Drive Spark Plug Sockets
 - ⁵/₈ in.
 - $^{13}/_{16}$ in.

- Metric
 - 1/4 in. Drive Regular, 6-point
 - 4 mm
 - 5 mm
 - 6 mm
 - 7 mm
 - 8 mm
 - 9 mm
 - 10 mm
 - 11 mm
- 1/4 in. Drive

Deep Well, 6-point

- 6 mm
- 7 mm
- 8 mm
- 9 mm
- 3/8 in. Drive

Regular, 6-point

- 9 mm
- 10 mm 11 mm
- 12 mm
- 13 mm
- 14 mm
- 15 mm
- 16 mm 17 mm
- 19 mm
- 3/8 in. Drive

Regular, 6-point

- 7 mm
- 9 mm
- 10 mm
- 11 mm
- 12 mm
- 13 mm
- 14 mm
- 15 mm
- 17 mm

3/8 in. Drive Regular, 6-point

- 10 mm
- 11 mm
- 12 mm
- 14 mm

Socket Extensions

- 1/4 in. Drive x 6 in. L
- ³/₈ in. Drive x 3 in. L
- 3/8 in. Drive x 6 in. L

Ratchets

- ¹/₄ in. Drive
- 3/8 in. Drive

Adapter

• ³/₈ in. Drive Female to 1/4 in. Drive Male

Screwdrivers

- Philips
- #0 x 75 mm
- #1 x 75 mm
- #2 x 38 mm
- #2 x 100 mm

Slotted

- #3 x 75 mm
- #5 x 75 mm
- #6 x 38 mm
- #6 x 100 mm

Precision

Screwdrivers

- **Philips**
 - #0
- #1

Slotted

- 1.4 mm
- 2.0 mm
- 2.4 mm 3.0 mm

Allen wrenches

- SAE
 - $^{1}/_{16}$ in.
 - $^{5}/_{64}$ in.
 - $^{3}/_{32}$ in.
 - $^{1}/_{8}$ in.
 - $^{5}/_{32}$ in.
 - $^{3}/_{16}$ in.
 - $^{7}/_{32}$ in.
 - $^{1}/_{4}$ in.
- Metric
- 1.5 mm
- 2 mm
- 2.5 mm
- 3 mm
- 4 mm
- 5 mm
- 5.5 mm
- 6 mm

Pliers

- Cutting: 6 1/4 in. L
- Diagonal: 6 ¹/₂ in. L with a wire cutter
- Needle nose: 6 1/2 in. L with a wire cutter

Wrenches

- Adjustable:
 - 8 in. L x 1 in. (25.4 mm) Max Width
- SAE
 - $^{3}/_{8}$ in.
 - $^{7}/_{16}$ in.
 - $^{1}/_{2}$ in.
 - 9/₁₆ in.
 - ⁵/₈ in.
 - ¹¹/₁₆ in.

Metric

- 9 mm
- 10 mm 11 mm
- 13 mm
- 15 mm
- 17 mm

Bit set (1/4 in. Drive)

- Bit driver
 - (70 mm shaft length)
- **Bits**
 - **Philips**
 - (1) PH0
 - (3) PH1
 - (3) PH2
 - (3) PH3
 - Slotted
 - (2) #3
 - (2) #4
 - (2) #5
 - (2) #6
 - (2) #7
 - Posi-Drive
 - (1) PZ0
 - (3) PZ1
 - (3) PZ2
 - (3) PZ3
 - Hex
 - H2
 - H3
 - H4
 - H5
 - H6
 - Square
 - (1) S0
 - (1) S1
 - (2) S2
 - (1) S3

 - **Torx**
 - (2) T10
 - (2) T15
 - (2) T20
 - (1) T25
 - (1) T30
 - (1) T40
 - Adapter
 - 6-point to 1/4 in. Drive

