

MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

FUEL CELL SAFETY FOAM

Synonyms:

15356 JEGS FUEL CELL SAFETY FOAM

Company Identification

JEGS Automotive Inc. 101 Jegs Place Delaware, OH 43015

PHONE: 1-800-345-4545 WEBSITE: www.jegs.com

MSDS Number

None

Synonyms

None

Generic/Chemical Name

Flexible Polyurethane Foam

Product Type

Flexible Polyurethane Foam

Preparation Date

07/17/02

Transportation Emergency Responsewww.jegs.com/msds**Product Information**

Product Information and MSDS Requests: 1-800-345-4545

2. HAZARDOUS INGREDIENTS

COMPONENTS	CAS NUMBER	% by Weight	OSHA PEL/ACGIH TLV
Polyurethane Foam	9009-54-5	100%	None Established

Foamex polyurethane foam is a fully cross-linked reaction product of polyhydroxy polyol, toluene di-isocyanate, catalysts, surfactants, pigments and water. Polyurethane foam product is a polymeric material consisting of repeating units of carbon, hydrogen, oxygen and nitrogen.

3. PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point:	Not Applicable	Density:	0.5-40 lbs/cft
Vapor Pressure (mm Hg):	Not Applicable	Melting Point:	350 - 375°F
Vapor Density:	Not Applicable	Evaporation Rate:	Not Applicable

Solubility in Water: Insoluble**Appearance and Odor:** Uniform cellular solid structure of varying colors with slight characteristic odor.

4. FIRE AND EXPLOSION HAZARD DATA

Flash Point:	Decomposition products flash at > 500°F	LEL:	None
Flammable Limits:	None Applicable	UEL:	None
Classification:	Combustible Solid		
NFPA Sprinkler Classification:	Extra Hazard		
Extinguishing Media:	Dry Chemical; Water; Carbon Dioxide		
Special Fire Fighting Procedures:	Wear self-contained breathing apparatus in enclosed areas.		
Unusual Fire & Explosion Hazards:	If ignited, foam can produce rapid flame spread, intense heat, dense black smoke and toxic gases. Material can melt into a burning liquid that can drip and flow. Accumulated polyurethane dust can be readily ignited and presents a fire risk. High concentrations of dust in the air can explode if exposed to a flame, spark or other ignition sources.		

5. REACTIVITY DATA

Stability:	Stable
Conditions To Avoid:	High temperature, open flames; strong oxidizers (i.e. hypochlorite's)
Incompatibility:	High temperatures (above 249°C (480°F))
Hazardous Decomposition Products:	Strong oxidizing acids – will degrade
Hazardous Polymerization:	Will not occur.

6. HEALTH HAZARD DATA

Routes of Entry:	Inhalation – Foam dust	
Health Hazards:	Course dust can cause mechanical irritation of lungs and eyes. Airborne dust is evaluated as a nuisance dust. If ignited, foam may decompose and emit toxic gases and respiratory irritants.	
	Eye – Foam dust	
	Coarse dust can cause mechanical irritation to the eyes. If exposed, avoid rubbing eyes.	
Carcinogenicity:	NTP:	No
	IARC Cancer Review:	No
	OSHA Regulated:	No
Medial Conditions Aggravated by Exposure:	None Known	
Emergency First Aid Procedures:	Inhalation:	Remove to fresh air; contact physician if respiratory discomfort persists.
	Eyes:	Flush eyes thoroughly with water for 15 minutes.
	Skin:	None necessary
	Ingestion:	None necessary

7. PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be taken in Case Material is Released or Spilled:	No special response required---sweep up.
Waste Disposal Method:	Federal, state and local authorities should be contacted before attempting any form of disposal.
Safe Handling and Storage:	Warehousing of bun stock, sheets, rolls and fabricated items should be stored under a fusible sprinkler system with a minimum of six feet clearance between stacks of foam and the sprinkler heads Do not store foam near any ignition sources such as exposed electrical or gas heating elements, open flames and exposed lights. Do not smoke in foam storage areas. Do not allow foam scarp and cuttings to accumulate and maintain clear aisles with adequate access to all storage areas and exits.
Other Precautions:	Notify local fire companies of presence of large quantities of foam.

8. CONTROL MEASURES

Ventilation:	Local exhaust ventilation is recommended for those processing procedures that may generate foam dust and decomposition products. Examples of these processes include sawing, grinding, buffing and flame lamination, hot wire cutting, heat sealing and hot stamping.
Respiratory Protection:	Should be selected based on identity and concentration of air contaminant. Only NIOSH-approved respirators for protection against the air contaminant of concern should be used.
Eye Protection:	Recommended for those processing operations that may generate dust.

9. SPECIAL INFORMATION

Flexible polyurethane foam, like all organic materials, will burn if exposed to a sufficient heat source. The ignition temperature of polyurethane foam will vary depending on the product chemical formulation, but all polyurethane foams are combustible and can create fire risk. Flexible polyurethane foams, once ignited, may degrade and melt to a combustible liquid, which may add to the fire involvement.

Terms such as “fire retardant”, “slow burning” and “ flame resistant” describe certain flammability properties and should not be regarded as denoting fire safety under all conditions. Small-scale fire test are not intended to reflect hazards presented by these or any other material under real fire conditions.

Thermal decomposition products from polyurethane foams can be toxic and present a risk to humans who are exposed. This is true for all organic materials. Fire risks in varying degrees are common to all fires: heat; carbon monoxide, other toxicants, oxygen depletion and smoke. In fires involving polyurethane foam, particularly flexible foams, large quantities of dense smoke can be generated quickly.

Personnel involved in fire-fighting should wear self-contained breathing apparatus and be aware of the exposure to toxic and potentially lethal gases. Standard fire-fighting equipment generally employed by authorized firemen is mandatory.

10. USERS RESPONSIBILITY

An MSDS such as this cannot be expected to cover all possible individual situations. The user has the responsibility to provide a safe workplace. All aspects of an individual operation should be examined to determine if, or where precautions – in addition to those described herein – are required. Any health hazard information contained herein should be passed on to your employees.

11. DISCLAIMER

The information presented herein has been compiled from sources considered to be dependable and is accurate to the best knowledge of JEGS Automotive Inc., makes no warranty whatsoever expressed or implied of merchantability or fitness for the particular purpose, regarding the accuracy of such data or the results to be obtained from the use thereof. JEGS Automotive Inc. assumes no legal responsibility for use or reliance upon this data. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.