DIRECTIONS 717 SUBARU FRONT

STEP #1. Remove the existing anti-sway bar. It is located to the rear of the wheels and the bar ends attach to the control struts.

STEP #2. NOTE: Due to the thicker steel of the ADDCO bar, it is not run up over the exhaust as there would be insufficient clearance between the exhaust pipe and the frame structure. Place the large D-shaped rubber bushings on the bar next to the shoulder bends and place bar in position. If the bar touches the exhaust, then insert the spacer between the bar bracket and bushings.

STEP#3. Using the existing nuts and bolts that held the original brackets, attach the two halves of the supplied two piece brackets loosely. Lift bar mid-section into position and close the bracket halves around the bushing. Start the center bolt to connect the two halves. Fully tighten the original bolts, and then return and tighten the center bolt until the assembly is secure.

STEP #4. Assemble the brackets and plates loosely to the bar eyes as illustrated (flat side of the bracket goes to the bar eye, the formed end is up and the base plate is outboard), using only the longer bolt that goes through the bar eye.

STEP #5. Slip the small D-shaped bushings around the control strut at the point that the original bar attached. With the car resting on it's front wheels, raise the bar ends up and close the bracket and base plate around the D-shaped bushing on the strut. Start the upper (shorter) bolt and lock-nut. Tighten all lock-nuts to 20ft/lbs.

STEP#6. After the installation is complete, bounce the car to check the clearance of all parts throughout the suspension travel distance.

STEP #7. Road test the car to familiarize yourself with its new handling. As we cannot supervise your installation or driving, we cannot be responsible for more than the cost of the kit. For best balance and control, this kit should be used in conjunction with our rear kit #352 (2wd) or #353 (4wd).

HARDWARE

2 RH 046C Brackets

2 RH 034 Plates

2 RH 031 Plates

2 RH O53 Brackets

2 UB 610 Bushings

2 UB 613B Bushings

4 RH 104 Washers

4 RH 304 Lock-Nuts

2 RH 214 Bolts

2 RH 226 Bolts