



Window Fur Channel Kits

INSTRUCTIONS

Installation of Fur Strips (3/8" Flat Dusters)

1. Remove old staples by twisting up end and cutting off. If the original fur is no longer present look for remains of old staples or staple holes for more accurate location of fur strips.
2. On the front doors no fur strip was used on the interior side, a roller #14790 was used. Some did not have any fur strip on either side, rollers were used #14790 on the interior side and #2082 on the exterior side. On the vehicles with fur, on the exterior door side place new fur strip which are located approximately 1-1/4" from the top edge of the door belt moulding #15671(DS) and #15672 (PS). Use the original staple holes to help you locate correct positioning. The fur strip was positioned low so no contact with the chrome window frame #1447 will accrue when window is rolled down.
3. Hold fur and drill a 5/64"(.078") hole at one end, and progress towards the other end. Space holes about 6" apart. Using screws supplied in kit to attach fur strip.
4. On the rear quarter window place new fur strips on both the garnish moulding and outer body trim, insuring that the stainless beading is even with the top just above the edge.
5. Hold fur and drill a 5/64"(.078") hole at one end, and progress towards the other end. Space holes closer on curved components. Using screws supplied to attach fur strip.

CAUTION: Do not start at each end and work toward center. Drill each hole one at a time and install screw. This insures more accurate alignment.

6. Twist heads of screws with screwdriver to sink it into fur pile. The head of the screw should draw into the pile enough so it becomes invisible.

Installation of Division Bar (Non-Flexible U-Channel)

1. The complete vent window assembly must be removed from the door. This is also a good time to replace the vent window seal, Our part # 565.
2. The Division Bar Channel originally came in two pieces The Division Bars Stops, part # 147 should be replaced at this time. Ours is one piece to simplify installation.
3. Drill out four rivets holding original fur channel. This will let the top part of the assembly to come apart. Install the new Division Bar, using hardware included in screw kit.

Installation of Moleskin (Flat Strip of Fur)

1. The Moleskin fits in the channel that is bolted to the back area of the door. The chrome frame # 1447 and door glass will slide up and down in it.
2. To install, remove old moleskin, degrease surface, and apply glue. You can use our # 036 3M Super Weather-strip Adhesive.

Kit Includes:

- A. 2 - Division Bar Channels 32"
- B. 2 - 3/8 Fur Strip 24"
- C. 2 - Moleskin 19x1-5/8" long
- D. 2 - 3/8 Inner Fur Strips 26"
- E. 2 - 3/8 Outer Fur Strips 24-3/4"
- 1 - Screw Kit

