
## INSTALLATION INSTRUCTION

88347 Exhaust Cross-Over Pipe Kit



2013-12 Jeep Wrangler, Wrangler Unlimited w/3.6L eng.



<u>P/N</u>	<u>DESCRIPTION</u>	QTY.
52512	Pipe	1
34200	U-Bolt Clamp	2
713356	Instructions	1




Illustration 1

WARNING – Do not attempt to cut exhaust while installed on vehicle; damage to oil pan, wiring and brake lines can result.

1)	☐ Park vehicle on a level surface. Set the parking brake and chock rear wheels. Disconnect the negative ground cable from the battery.
2)	$\square$ Raise the front of the vehicle and support the frame with jack stands.
3)	$\square$ Raise the rear of the vehicle and support the frame with jack stands.
4)	$\square$ If equipped, remove the transmission crossmember brace. See Illustration 1.
5)	☐ Loosen the rear crossover pipe to muffler pipe clamp. See Illustration 1.
6)	☐ Pry muffler pipe back to disengage from crossover pipe.
7)	☐ Remove bolts from driver and passenger side crossover pipe flanges. See Illustration 1.
8)	☐ Remove crossover pipe.



9)  $\square$  Mark and cut driver side of crossover pipe 10" from end of pipe. See Illustration 2.






Illustration 3

10) $\square$ Mark and cut passenger side of crossover pipe 5" from bend. See Illustration 3.
11) 🗆 Install driver side section of cut crossover pipe on muffler pipe. Make sure crossover pipe is fully engaged on muffler pipe
12) $\square$ Line up flanges and loosely install flange bolts. Tighten crossover pipe to muffler pipe clamp.
13)   Slide the 52512 exhaust pipe onto the cut end of driver side crossover pipe. Do not clamp.
14)   Slide cut end of passenger side crossover pipe into the 52512 exhaust pipe.
15) ☐ Line up flanges and loosely install flange bolts.

16) ☐ Install and tighten supplied clamps. Align driver side clamp so nuts face to the side toward the driveshaft. Align passenger side clamp so nuts face down. See illustration 4.






Illustration 4

17) 

Tighten four flange bolts. Re-torque all clamps.



Installed Dynomax Crossover Pipe