



PERFORMER RPM HYDRAULIC ROLLER CAMSHAFT
For 348/409 'W' Big Block Series Chevrolet V8 Engines
Part #2268
INSTALLATION INSTRUCTIONS

PLEASE study these instructions carefully before beginning this installation. Most installations can be accomplished with common tools and procedures. However, you should be familiar with and comfortable working on your vehicle. If you do not feel comfortable performing this installation, it is recommended to have the installation completed by a qualified mechanic. If you have any questions, please call our **Technical Hotline at: 1-800-416-8628**, 7:00 am - 5:00 pm, Pacific Standard Time, Monday through Friday.

IMPORTANT NOTE: Proper installation is the responsibility of the installer. Improper installation will void your warranty and may result in poor performance and engine or vehicle damage.

DESCRIPTION: Edelbrock Performer RPM hydraulic roller camshafts are designed specifically for use with the corresponding Performer RPM manifold. The Performer RPM manifold #7158 (for stock small port heads), or Performer RPM #7159 (for large port heads, including Edelbrock RPM heads #60819), and Performer RPM Hydraulic Roller camshaft are designed to work together to give you better driveability and performance. The #2268 is designed for use with 'W' series engines that were equipped with flat tappet lifters from the factory, and will use a thrust button to hold the cam in place. For best results, use the Edelbrock manifold/camshaft package with the recommended carburetor and headers. Performer RPM camshafts are designed for use with modified or high performance cylinder heads and valve train components only. Screw-in studs, adjustable rocker arms, and matching valve springs must be used. **NOTE:** This camshaft is manufactured from **steel billet** and will require the use of a **bronze distributor gear** to prevent engine damage.

IMPORTANT: This instruction sheet provides general installation guidelines which can affect your warranty. Read it carefully. It is not our intent to cover each detail of installation here; a step-by-step procedure manual would be far too lengthy. We want to caution you that installing a camshaft is a complicated procedure that requires a good general knowledge of automotive engines. If you are not confident that you can complete the camshaft installation successfully, we suggest you consider having it installed by a qualified mechanic. Improper installation will result in **LOW MILEAGE, POOR PERFORMANCE, COSTLY REINSTALLATION, and ENGINE DAMAGE.**

TO AVOID THESE PROBLEMS, YOU MUST DO THE FOLLOWING:

1. Carefully study and understand all instructions.
2. Examine the camshaft for possible shipping damage (if damaged contact your dealer immediately).

KIT CONTENTS:

- 1 Camshaft
- 1 Assembly Lube

PREPARATION CHECKLIST

TOOLS AND EQUIPMENT FOR INSTALLATION:

- | | | |
|---|--|--|
| <input type="checkbox"/> Box and open end wrenches | <input type="checkbox"/> Torque wrench | <input type="checkbox"/> Water bucket |
| <input type="checkbox"/> Socket set | <input type="checkbox"/> Hammer | <input type="checkbox"/> Harmonic balancer puller & installer |
| <input type="checkbox"/> Distributor wrench | <input type="checkbox"/> Gasket scraper or putty knife | <input type="checkbox"/> Gear puller for crankshaft sprocket |
| <input type="checkbox"/> Pliers (channel locks & hose clamp) | <input type="checkbox"/> Timing light & vacuum gauge | <input type="checkbox"/> Chalk, paper and pencil |
| <input type="checkbox"/> Screw drivers (regular and phillips) | <input type="checkbox"/> Rags | <input type="checkbox"/> Masking tape (for tagging hoses and electrical wires) |

HARDWARE AND PARTS REQUIRED:

- | | |
|---|--|
| <input type="checkbox"/> Edelbrock Roller Lifters #97383 or equivalent | <input type="checkbox"/> Timing Cover Gasket and Front Seal |
| <input type="checkbox"/> Push Rods designed for Roller Lifters #9635 | <input type="checkbox"/> Engine oil and filter |
| <input type="checkbox"/> Camshaft thrust button (For #2263) | <input type="checkbox"/> Radiator coolant |
| <input type="checkbox"/> Gaskets - Intake #7240 (large port) or #7242 (small port), Valve Cover #7582 | <input type="checkbox"/> Timing Chain and Gear Set |
| <input type="checkbox"/> Pipe plugs, if needed | <input type="checkbox"/> Front cover oil seal, OEM or equivalent |
| <input type="checkbox"/> Edelbrock Gasgacinch #9300 | <input type="checkbox"/> Valve Springs with a closed pressure of 120-130 lbs, open pressure of 320-340 lbs and a max lift of .700" |
| <input type="checkbox"/> RTV Silicone sealer | <input type="checkbox"/> Bronze Distributor Gear |

IMPORTANT NOTES AFFECTING YOUR WARRANTY. PLEASE READ BEFORE CONTINUING THIS INSTALLATION!

CAM LOBE DAMAGE: Cam lobe wear is almost non-existent unless mismatched parts are used or installation of the cam and lifters is done improperly. Cam damage can result from the timing gear loosening due to improper torque on bolts. Bolts holding gear to camshaft should be torqued carefully and a locking compound applied to threads of bolts. Before installing your new camshaft, check the gear drive on the distributor and oil pump for any signs of wear. If worn, be sure to replace with a new gear or you may wear out your camshaft prematurely. You must use a bronze distributor gear with this camshaft to prevent engine damage. High-pressure oil pumps are not recommended with Performer RPM hydraulic roller camshafts.

VALVE SPRINGS (CAUTION REGARDING YOUR WARRANTY): In order for this Performer RPM roller cam to be covered under ANY WARRANTY, you MUST use the correct valve springs. Failure to install the correct valve springs may cause lifters not to follow the cam lobes and damage engine parts.

1. This camshaft is designed to function with valve springs that have a closed pressure of 120-130 lbs, open pressure of 320-340 lbs and a max lift of .700". Special retainers may be necessary with your installation for proper spring height. Do not use rotator type valve springs or retainers for this application.

CAM GEARS AND CAMSHAFT END PLAY: If cam gear becomes loose, the cam will slide back in the block, causing the lifters to hit the lobes next to them and also the cam bearing journals. If the engine is run after this happens, the bottom of the lifters and the sides of the lobes will become damaged. Therefore, a thrust button must be used to control end play. See Installation Instructions section for end play specifications.

LIFTERS: Retrofit roller lifters must be used with this camshaft. Edelbrock roller lifter kit #97383 is designed to work with this camshaft. To install your roller lifters, use fresh clean oil on the lifter and the lifter bore just prior to installing. The guide bar (high side of tappet) must face the opposite side of block. See roller lifter instructions for additional information.

PUSHRODS AND ROCKER ARMS: High performance pushrods, rocker arms, and studs are recommended for this installation. After the cam is installed and timed correctly (**See Figure 2**), it will be necessary to check each pushrod for correct lifter preload.

TIMING CHAIN: An appropriate stock or aftermarket Timing Chain and Gear Set or gear drive must be used. Inspect the timing chain and gears for signs of wear or damage before installing.

OPERATING CLEARANCES: When installing a camshaft, it is always important to check for proper operating clearances, especially when high performance components are used. Things to look for that can cause failure and damaged parts are as follows:

1. Improper valve-to-piston clearance (this should be no less than 0.080").
2. Rocker arm stud slot clearance (both ends; valve closed and open).
NOTE: We recommend the use of roller rockers.
3. Proper valve spring installed height. Correct dimensions mean maximum performance and longer engine life.

REMOVAL OF ENGINE PARTS BEFORE CAMSHAFT INSTALLATION

(Be sure to keep all parts in order)

WARNING! DO NOT REMOVE RADIATOR CAP OR RADIATOR HOSES WHILE ENGINE IS HOT!

IMPORTANT NOTICE: If the air conditioning condenser needs to be removed to provide clearance for camshaft removal, have the system evacuated by an appropriate repair facility **BEFORE** starting the installation. The facility can recharge the system after installation.

1. Disconnect the battery.
2. Drain radiator coolant. Drain plug will normally be located on lower right or left side of the radiator facing the engine.
3. Move fan shroud back and remove fan and spacer from water pump. On air conditioned vehicles, remove bolt, lower idler pulley and compressor-to- water pump mount. Disconnect hoses and brackets. Most vehicles will require radiator removal prior to cam removal. Remove water pump.
4. Remove radiator and air conditioning condenser if so equipped. In some cases, the front grille may have to be removed. Measure distance from front cover to grille or brackets that may interfere with camshaft against the length of the camshaft.
5. Remove the gas cap to relieve pressure. Disconnect fuel line and plug the line. Replace gas cap.
6. Disconnect all linkage from carburetor such as throttle, throttle springs, transmission, cruise control and automatic choke.
7. Tag and remove coil wires and sensor wires.
8. Tag and remove vacuum lines.
9. Remove valve covers.
10. Remove distributor cap and wires, rotate engine until rotor points towards number 1 terminal in cap and pointer on front cover is on top dead center (TDC) and remove distributor (**See Fig. 1**). Make a note of the approximate position of the distributor housing in relation to the manifold to assist in getting the distributor properly located during re-installation.
11. Remove carburetor and intake manifold assembly. Remove and discard intake manifold gasket.

12. Remove rocker arms and pushrods.
13. Remove hydraulic valve lifters.
14. Remove crankshaft pulley, and using a suitable puller, remove crankshaft dampener (harmonic balancer).
15. Loosen oil pan and remove water pump and front cover.

NOTE: *The front cover oil seal should be replaced before the front cover is re-installed.*
16. Remove fuel pump and fuel pump pushrod (vehicles with mechanical fuel pumps only).
17. Rotate engine until timing marks are aligned (**See Fig. 2**).
18. Remove bolts retaining camshaft sprocket. Remove sprocket and chain.
19. Remove camshaft.
20. Using appropriate gear puller, remove crankshaft sprocket.

INSTALLATION PROCEDURE

1. Check lifters as covered in Lifters section. Coat cam lobes with fresh clean oil. Lube distributor drive of cam with assembly lube (supplied).
2. Install new camshaft with new sprockets and timing chain. Torque to 25 ft/lbs.

NOTE: *Roller cams require the use of a cam thrust button spacer to control camshaft end play when installed in blocks originally equipped with a flat tappet cam. Check camshaft end-play, maintain between .005" and .010". This must be checked with the timing cover, thrust button and gasket in place, just as it would be after final assembly without the roller lifters installed.*

CAUTION: *When installing your timing chain and gear set, it is necessary to check camshaft position for correct timing alignment. This requires indexing the camshaft with a degree wheel to verify timing alignment. OEM timing gear sets are not recommended for use with Edelbrock camshafts. Use locking compound material on bolt threads holding gear to cam. Torque to factory specification listed in Motors or other repair manual.*
3. Install front timing cover and oil pan once proper end play has been achieved.

NOTE: *Install new seal between oil pan and front cover if old seal is damaged after removal. Use RTV silicone sealant on seal to ensure proper seal to pan.*
4. Install your roller lifters using fresh clean oil on the lifter and the lifter bore just prior to installing. Check to make sure all lifters fit freely in lifter bores.

NOTE: DO NOT *soak lifters in oil, or "pump up" lifters prior to installation. This will result in improper lifter preload.*
5. Line up camshaft with timing marks aligned (**See Fig. 2**).
6. **VALVE ADJUSTMENT:**
 - A. Install pushrods with lube on both ends, making sure the pushrod tip hits the center of the lifter cup. Install rocker arms, but do not tighten the adjusting nuts. You are now ready to start valve adjustment.
 - B. Turn the engine over until cylinder #1 reaches TDC on the compression stroke (both valves are closed). Then install the adjusting nuts on both the intake and exhaust rocker arms and adjust them to zero clearance between the rocker arm and valve tip. Edelbrock retro-fit roller lifters should be tightened a further 3/4 - 1 full turn to achieve the correct pre-load. If using another brand or OEM lifters, you will want to refer to the appropriate manufacturer documentation.
 - C. Rotate the crankshaft 90 degrees so that the next piston in the firing order is at TDC and repeat step #2. Continue turning the crankshaft and proceeding to the next cylinder in the firing order until all the rockers have been set.
7. Torque front timing cover bolts to 6-7 ft. lbs.
8. Install front harmonic balancer and torque to 60 ft.-lbs.
9. Install fuel pump and a pump pushrod equipped with a bronze tip.
10. Install water pump using new gaskets and torque to 30 ft.-lbs.
11. Install intake manifold/carburetor assembly using new intake gasket set and torque bolts to 25 ft/lbs.
12. **DISTRIBUTOR INSTALLATION & ENGINE TIMING**

NOTE: *This camshaft requires the use of a bronze distributor gear to prevent engine damage. Use only OEM style oil pump drive gears.*

- A. Turn the engine over in direction of rotation until the No. 1 intake valve closes and continue until the pointer on the front cover is approximately five degrees (5°) before top dead center (BTDC) (**See Fig. 1 for firing order**).
 - B. Re-install the distributor with the rotor pointing towards #1 terminal in the cap, and with the distributor housing in its original position. If distributor will not drop down all the way to the flange on the manifold, it will be necessary to align the distributor shaft with the oil pump drive. Slowly rotate the engine until the distributor drops down against the manifold, then continue turning until two complete revolutions are completed and the timing marks once again come to five degrees BTDC.
 - C. Lightly tighten the hold-down clamp so that the distributor can still be turned to determine final setting using a timing light with the engine running.
13. Replace valve covers, carburetor linkage and remaining vacuum and electrical connections.
 14. Re-install air conditioner, if so equipped.
 15. Refill radiator with coolant and re-connect battery.
 16. Double check all connections, fuel lines, etc. before starting engine.
 17. Engine oil and filter should be changed before start-up.


CAMSHAFT & LIFTER RUN-IN: Standard camshaft run-in is not required when using a roller cam.

SPECIAL INSTRUCTIONS: With the Edelbrock manifold and camshaft package installation, a carburetor jet change and ignition timing changes may be required for best performance. Due to the varied applications of years and models of vehicles, no one combination could suffice for all installations. The following procedures are only a guideline.

- **IGNITION TIMING:** Increase initial setting to 12-14° BTDC (Before Top Dead Center). Total advance not to exceed 34-36°. With initial and centrifugal weights combined, timing should be at full advance by 3200-3500 rpm. After timing is adjusted, re-connect the vacuum advance line.

NOTE: The best combination for any particular vehicle or application must be determined by trial and error using the above information as a guideline.

- **HEADERS:** For best performance, headers are recommended. For this application, primary tube diameter should be 1-3/4" or larger. The remainder of the exhaust system should consist of dual exhaust and tail pipes, at least 3" in diameter, with free-flowing mufflers. These recommendations may vary depending on your specific application.



**Figure 1 - 348-409 C.I.D. Chevrolet V8
Firing Order and Timing Marks
Firing Order: 1-8-4-3-6-5-7-2**

Turn distributor counter clockwise to advance timing




Figure 2 - Timing Chain Sprocket Alignment

WARNING

In order for this Performer RPM cam and lifter kit to be covered under ANY WARRANTY, you MUST use the correct specification valve springs. Failure to install the correct valve springs may cause lifters not to follow the cam lobes and damage engine parts.

IF YOU HAVE ANY QUESTIONS ABOUT THIS APPLICATION, PLEASE CONTACT OUR TECHNICAL DEPARTMENT IMMEDIATELY.



**Edelbrock Corporation • 2700 California St. • Torrance, CA 90503
Tech-Line: 1-800-416-8628 • Sales/Office Line: 310-781-2222**