

EDELBROCK 14" AIR CLEANER W/ BREATHABLE LID PART NUMBERS: 43660, 43661, 43662

INSTALLATION INSTRUCTIONS

HOOD CLEARANCE

Figure #1

Please study these instructions carefully before installing your new Air Cleaner Assembly. If you have any questions, do not hesitate to contact our **Technical Hotline at: (800) 416-8628** from 7:00 am to 5:00 pm, Monday through Friday, Pacific Standard Time.

Please note that the Edelbrock Air Cleaner is a universal part and may require some modifications to fit your specific application.

KIT CONTENT:

(1) Breathable Air Cleaner Lid

(1) Reusable Filter Element

(1) Air Cleaner Stud, Washer and Nut

CLAY CONES

(1) Air Cleaner Base

(1) Air Cleaner Gasket

INSTALLATION INSTRUCTIONS:

- Remove the previously installed air cleaner and air cleaner stud if not already done.
- 2. Install the supplied air cleaner gasket onto the carburetor and place the new air cleaner base onto the air cleaner gasket.
- 3. Thread the supplied air cleaner stud into the carburetor until the stud bottoms out. Install the filter element and air cleaner lid to verify that the air cleaner stud protrudes about 3/8" above the lid. Trim air cleaner stud, if necessary.

NOTE: For carburetors with tall bowl vent tubes, the use of Edelbrock air cleaner spacer, #8092, may be required. Vent tube, to air cleaner clearance, should be no less than 1/8".


- **4.** To prevent possible hood damage, check for proper hood clearance using clay cones as seen in Figure #1. **Don't shut the hood without checking clearance first!**
- 5. Secure the air cleaner to the air cleaner stud using the supplied air cleaner nut and washer.





Some applications may require a Crankcase Ventilation Adapter #1205 (sold separately) that mounts to the lower side of the air cleaner per the recess seen in Figure #2. This Crankcase Ventilation Adapter can be purchased at your local Edelbrock retailer.

- 1. If you wish to use the crankcase ventilation adapter, drill two ¼" bolt holes (A) in the recessed area at the rear of the air cleaner base, then drill a few ¼" holes (B) in the larger recess window to allow the fitting to breath (See Figure #2). Bolt the fitting to the base with the ¼" nuts, bolts, and washers included with #1205. Be sure to de-burr drilled holes before installing the adapter.
- 2. Check for clearance between linkages and the ventilation adapter and rotate the air cleaner base as necessary.



FILTER ELEMENT MAINTENANCE:

These Breathable Air Cleaners are equipped with pre-oiled, cotton gauze elements and lids which are reusable.

To clean the filter element and lid, we recommend using the Edelbrock Pro-Charge[™] Air Filter Cleaning Kit (#43600) to clean and re-oil your Breathable Air Cleaners. The cleaning kit is specifically formulated with clear oil that will not damage the dyed cotton gauze elements. **NOTE: Make sure to let the air filter element dry completely before apply the oil.**

Replacement 14" round air cleaner elements (Edelbrock #43666 Red, 43664 Blue, 43665 Black) and breathable lids (Edelbrock #43663 Red, 43664 Blue, 43665 Black) are available through your local retailer.