



**2012 Mustang Boss 302 Laguna Seca Edition
Splitter M-16601P-MB
INSTALLATION INSTRUCTIONS**

NO PART OF THIS DOCUMENT MAY BE REPRODUCED WITHOUT PRIOR AGREEMENT AND WRITTEN PERMISSION OF
FORD RACING PERFORMANCE PARTS

!!! PLEASE READ THE FOLLOWING INSTRUCTIONS CAREFULLY PRIOR TO INSTALLATION !!!

Caution: If you are not confident that you can complete the installation safely, have it completed by a certified technician! Failure to complete the installation correctly could cause damage to your vehicle.

**The following instructions apply to a 2012 Mustang Boss 302
Laguna Seca Edition.**

**Before proceeding the standard splitter must be removed by removing
the (16) bolts and (10) push pins located on the underside of the
splitter.**

**PLEASE NOTE: The Laguna Seca Edition splitter is intended for use
on closed courses only and is NOT street legal. The Laguna Seca
Edition splitter must be removed prior to driving on public roads. Ford
recommends re-installing the standard splitter for use on public roads.**

Techline (800) FORD788

Factory Ford shop manuals are available from Helm Publications, 1-800-782-4356



2012 Mustang Boss 302 Laguna Seca Edition Splitter M-16601P-MB INSTALLATION INSTRUCTIONS

NO PART OF THIS DOCUMENT MAY BE REPRODUCED WITHOUT PRIOR AGREEMENT AND WRITTEN PERMISSION OF FORD RACING PERFORMANCE PARTS



PARTS IN KIT:

Quantity	Part Name
1	Splitter
2	Splitter support rod assembly
20	M8 X 25mm bolt
4	J-Nut

Techline (800) FORD788

Factory Ford shop manuals are available from Helm Publications, 1-800-782-4356



2012 Mustang Boss 302 Laguna Seca Edition Splitter M-16601P-MB INSTALLATION INSTRUCTIONS

NO PART OF THIS DOCUMENT MAY BE REPRODUCED WITHOUT PRIOR AGREEMENT AND WRITTEN PERMISSION OF FORD RACING PERFORMANCE PARTS

INSTALLATION INSTRUCTIONS:

STEP 1: Support the vehicle to gain access to the undercarriage.

STEP 2: Remove the (4) bottom clips on the leading forward edge of the splash guard and replace with the provided J-Nuts.



STEP 3: Loosely install the splitter with the provided (20) fasteners; torque each fastener to 28 in.-lb. beginning with center-most fastener and working outward on both sides.



Techline (800) FORD788

Factory Ford shop manuals are available from Helm Publications, 1-800-782-4356



2012 Mustang Boss 302 Laguna Seca Edition Splitter M-16601P-MB INSTALLATION INSTRUCTIONS

NO PART OF THIS DOCUMENT MAY BE REPRODUCED WITHOUT PRIOR AGREEMENT AND WRITTEN PERMISSION OF FORD RACING PERFORMANCE PARTS

- STEP 4:** Locate and remove caps at the center of the top surface on the lower grille opening, then install one upper splitter rod end through each hole in the lower grille opening and thread into bumper bracket.



- STEP 5:** Install the splitter support rods onto rod ends; torque bolts through splitter to 28 in.-lb.



- STEP 6:** Lower vehicle back to ground. With vehicle at factory ride height, adjust the splitter support rods so the splitter is level and tighten jam nuts.



Techline (800) FORD788

Factory Ford shop manuals are available from Helm Publications, 1-800-782-4356