

Dodge Ram 1500 2WD/4WD 1.5" Rear Coil Spring Spacer

Parts:

2 - Coil Spacers

PRE-INSTALLATION

Professional installation by a certified technician is strongly recommended.

Not responsible for altered products. No claims are made regarding any lifting devices. Any and all claims implied in this document excluded.

NOTES:

Check spacers regularly to ensure tightness.

REQUIRED TOOLS:

Floor Jack

Jack Stands

Impact Wrench/Socket

INSTALLATION INSTRUCTIONS

STEP 1: Chock front wheels and jack up vehicle.

STEP 2: Place jack stands under frame rails.

STEP 3: With vehicle on stands, use floor jack to support rear suspension.

STEP 4: Remove rear track bar bolt.

STEP 5: Disconnect upper sway bar end links.

STEP 6: Disconnect ABS lines to avoid damage.

STEP 7: Remove lower shock mounting hardware.

STEP 8: Lower axle with floor jack and remove stock coil spring and stock rubber coil isolator.

STEP 9: Use included hardware to fasten new spacer to upper mount location and tighten.

STEP 10: Re-install stock rubber isolator and coil spring.

STEP 11: Raise suspension.

STEP 12: Reattach shock in lower mount.

STEP 13: Reinstall upper sway bar end links and track bar bolt.

STEP 14: Reconnect ABS lines.

STEP 15: Lower vehicle.

POST-INSTALLATION

STEP 1: Check for proper torque on all fasteners.

STEP 2: Readjust headlights to proper alignment.

MAINTENANCE: After 500 miles, re-torque all fasteners. (Recommended every 1000 miles thereafter) Have all suspension, driveline and steering components inspected by a certified technician during routine maintenance (Recommended every 3000 miles)