

20-inch Dual Row LED Light Bar Hood Mounting Brackets
Jeep: 07-12 Wrangler JK 4WD,
07-12 Wrangler Unlimited JK 4WD/2WD

Parts:

- 1 - Driver Side Bracket
- 1 - Passenger Side Bracket
- 2 - Spacers
- 2 - Rubber Spacer Pads
- 4 - 8mm Button-Head Bolts

PRE-INSTALLATION

Professional installation by a certified technician is strongly recommended.

Not responsible for altered products. No claims are made regarding any after-market devices. Any and all claims implied in this document excluded.

NOTES:

Light bar not included in kit.

REQUIRED TOOLS:

T-50 Wrench

6mm Allen Wrench

INSTALLATION INSTRUCTIONS

STEP 1: Disconnect positive battery lead before installation.

STEP 2: Remove two factory bolts on hood hinge. (T-50 Wrench)

STEP 3: Remove backing from rubber pad and apply to bracket spacer.

STEP 4: Place spacer (rubber pad down) over mounting holes on hinge.

STEP 5: Place bracket on top of spacer and align mounting holes.

STEP 6: Secure with included 8mm button-head bolts. Torque to factory specs. (6mm Allen Wrench)

STEP 7: Repeat process on other side.

STEP 8: Install light bar in bracket using hardware included with kit.

STEP 9: Wire power to lights per instructions supplied with kit.

STEP 10: Reconnect positive battery lead.

POST-INSTALLATION

MAINTENANCE: Periodically check to ensure that all fasteners are properly tightened.